

Daikin Altherma 3 R MT W

Wall mounted **reversible** air to water heat pump for heating and cooling

- › Quick configuration in 9 steps in a high resolution colour interface wizard
- › Compact dimensions allows for small installation space, as almost no side clearances are required.
- › Combine with a stainless steel tank or ECH₂O thermal store.
- › Inclusion of all hydraulic components means no third party components are required
- › The unit's sleek design blends in with other household appliances



011-1W0651
011-1W0653
011-1W0655

Efficiency data				ELBX + ERRA	12E6V/9W + 08EW1	12E6V/9W + 08EV3	12E6V/9W + 10EW1	12E6V/9W + 10EV3	12E6V/9W + 12EW1	12E6V/9W + 12EV3
	Space heating	Average climate water outlet 55 °C	General	SCOP	3,47	3,37	3,48	3,38	3,58	3,47
				η _s (Seasonal space heating efficiency)	136	132	136	132	140	136
				Seasonal space heating eff. class	A++					
	Average climate water outlet 35 °C	General	SCOP	4,95	4,79	4,98	4,82	4,98	4,82	
			η _s (Seasonal space heating efficiency)	195	188	196	190	196	190	
			Seasonal space heating eff. class	A+++						
Indoor Unit				ELBX	12E6V	12E9W	12E6V	12E9W	12E6V	12E9W
Casing	Colour				White + Black					
	Material				Resin, sheet metal					
Dimensions	Unit	HeightxWidthxDepth		mm	840 x 440 x 390					
Weight	Unit			kg	48,5					
Operation range	Heating	Ambient	Min.~Max.	°C	-25 ~25					
		Water side	Min.~Max.	°C	15 ~65					
	Domestic hot water	Ambient	Min.~Max.	°C	-25 ~35					
		Water side	Min.~Max.	°C	25 ~62					
Sound power level	Nom.			dB(A)	44					
Sound pressure level	Nom.			dB(A)	30					
Outdoor Unit				ERRA	08EW1	08EV3	10EW1	10EV3	12EW1	12EV3
Dimensions	Unit	HeightxWidthxDepth		mm	1,003 x 1,270 x 533					
Weight	Unit			kg	107					
Compressor	Quantity				1					
	Type				Hermetically sealed swing compressor					
Operation range	Heating	Min.~Max.		°CDB	-25 ~ 25					
	Domestic hot water	Min.~Max.		°CDB	-25 ~ 35					
Refrigerant	Type				R-32					
	GWP				675					
	Charge		kg		3,25					
	Charge		TCO _{Eq}		2,19					
	Control				Expansion valve					
LW(A) Sound power level (according to EN14825)					56	54	56	54	56	54
Sound pressure level (at 1 meter)	Nom.				41,1	40,6	41,1	40,6	41,1	40,6
Power supply	Name/Phase/Frequency/Voltage			Hz/V	W1/3~/50/400	V3/1~/50/230	W1/3~/50/400	V3/1~/50/230	W1/3~/50/400	V3/1~/50/230
Current	Recommended fuses			A	16	32	16	32	16	32

This product contains fluorinated greenhouse gases.